



WWW.WORLDOFINSLATORS.COM

číslo výkresu EPL	5340 02 000 5340 12 000 1721/M	5341 02 000 5341 12 000 1722/M	5341 22 000 5341 32 000 1756/M	5342 02 000 5342 12 000 1723/M	5342 22 000 5342 32 000 1757/M	5343 02 000 5343 12 000 1724/M	5343 22 000 5343 32 000 1758/M	5344 02 000 1725/M
typ type	typ 1 12 kV-250A/P1 12 kV-250A/P2	typ 2 12 kV-250A/P4 24 kV-250A/P2	typ 2/170 12 kV-250A/170/P4 24 kV-250A/170/P2	typ 3 24 kV-250A/P3 36 kV-250A/P1	typ 3/170 24 kV-250A/170/P3 36 kV-250A/170/P1	typ 4 24 kV-250A/P4 36 kV-250A/P3	typ 4/170 24 kV-250A/170/P4 36 kV-250A/170/P3	typ 5 36 kV-250A/P4
nominální proud nominal strom	A 250	250	250	250	250	250	250	250
hmotnost weight	kg 3.2	4.7	6.3	5.8	7.2	9.6	10.2	12.5
povrch. dráha. creep. distance.	mm 240	490	490	605	605	935	935	1165